

# Part of Thermo Fisher Scientific

# **Material Safety Data Sheet**

Creation Date 28-Apr-2009

Revision Date 07-Mar-2011

**Revision Number 3** 

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name** 

Acetone

Cat No.

A9-4; A9-20; A9-200; A11-1; A11-4; A11-20; A11-200; A11S-4; A16F-1GAL; A16P-1GAL; A16P-4; A16S-4; A16S-20; A18-1; A18-4; A18-20; A18-200; A18-200LC; A18-500; A18CU1300; A18FB-19; A18FB-50; A18FB-115; A18FB-200; A18P-4; A18POP-19; A18POPB-50; A18RB-19; A18RB-50; A18RB-115; A18RB-200; A18RS-28; A18RS-50; A18RS-115; A18RS-200; A18S-4; A18SK-4; A18SS-19; A18SS-28; A18SS-50; A18SS-115; A18SS-200; A19-1; A19-4; A19RS-115; A19RS-200; A40-4; A928-4; A929-1; A929-4; A929RS-19; A929RS-50; A929RS-200; A929SK-4; A929SS-28; A929SS-50; A929SS-115; A929SS-200; A946-4; A946-4LC; A946FB-200; A946RB-19; A946RB-50; A946RB-115; A946RB-200; A949-1; A949-4; A949CU-50; A949N-119; A949N-219; A949POP-19; A949RS-28; A949RS-50; A949RS-115; A949SK-1; A949SK-4; A949SS-19; A949SS-28; A949SS-50; A949SS-115; A949SS-200; BP2403-1; BP2403-4; BP2403-20; BP2404-1; BP2404-4; BP2404SK-1; BP2404SK-4; HC-300-1GAL;

22050131; 22050295

**Synonyms** 

2-Propanone; Dimethyl ketone; (Certified ACS, HPLC, OPTIMA, Histological, Spectranalyzed, NF/FCC/EP, Pesticide, Electronic, GC Resolv, SAFE-COTE)

**Recommended Use** 

Laboratory chemicals

Company Fisher Scientific One Reagent Lane Fair Lawn, NJ 07410 Tel: (201) 796-7100

**Emergency Telephone Number** CHEMTREC®, Inside the USA: 800-424-9300 CHEMTREC®, Outside the USA: 001-703-527-3887

### 2. HAZARDS IDENTIFICATION

# 2. HAZARDS IDENTIFICATION

# DANGER!

### **Emergency Overview**

Flammable liquid and vapor. Irritating to eyes and skin. May cause irritation of respiratory tract. Vapors may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

Appearance Colorless Physical State Liquid odor sweet

Target Organs Central nervous system (CNS), Eyes, Respiratory system, Skin, Kidney, Liver, spleen

**Potential Health Effects** 

**Acute Effects** 

**Principle Routes of Exposure** 

Eyes Irritating to eyes.

**Skin** Irritating to skin. May be harmful in contact with skin. Repeated exposure may cause skin

dryness or cracking.

**Inhalation** Inhalation may cause central nervous system effects. May cause drowsiness and dizziness.

May cause irritation of respiratory tract. May be harmful if inhaled.

**Ingestion** Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful

if swallowed.

Chronic Effects Experiments have shown reproductive toxicity effects on laboratory animals. May cause

adverse liver effects. May cause adverse kidney effects.

See Section 11 for additional Toxicological information.

Aggravated Medical Conditions Central nervous system disorders. Preexisting eye disorders. Skin disorders. Kidney disorders.

Liver disorders.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Haz/Non-haz

Component	CAS-No	Weight %
Acetone	67-64-1	>95

# 4. FIRST AID MEASURES

**Eye Contact** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain

medical attention.

**Skin Contact** Wash off immediately with plenty of water for at least 15 minutes. Obtain medical attention.

**Inhalation** Move to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately if

symptoms occur.

**Ingestion** Do not induce vomiting. Obtain medical attention.

Notes to Physician Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

### 5. FIRE-FIGHTING MEASURES

-20°C / -4°F **Flash Point** 

Method No information available.

**Autoignition Temperature** 465°C / 869°F

**Explosion Limits** 

Upper 12.8 vol % Lower 2.5 vol %

CO<sub>2</sub>, dry chemical, dry sand, alcohol-resistant foam. Cool closed Suitable Extinguishing Media

containers exposed to fire with water spray.

Unsuitable Extinguishing Media Water may be ineffective

No information available. **Hazardous Combustion Products** 

Sensitivity to mechanical impact No information available. Sensitivity to static discharge No information available.

**Specific Hazards Arising from the Chemical** 

Flammable. Risk of ignition. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

**Protective Equipment and Precautions for Firefighters** 

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

**NFPA** Health 1 Flammability 3 Instability 0 Physical hazards N/A

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protective equipment. Remove all sources of ignition. Take precautionary **Personal Precautions** 

measures against static discharges.

Should not be released into the environment. **Environmental Precautions** 

Up

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary measures against static discharges. Keep in suitable, closed containers for disposal..

### 7. HANDLING AND STORAGE

Handling Wear personal protective equipment. Keep away from open flames, hot surfaces and sources

> of ignition. Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against

static discharges.

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat Storage

and sources of ignition. Flammables area.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Engineering Measures**

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Exposure Guidelines**

Component	ACGIH TLV	OSHA PEL	NIOSH IDLH
Acetone	TWA: 500 ppm STEL: 750 ppm	(Vacated) TWA: 750 ppm (Vacated) TWA: 1800 mg/m³ (Vacated) STEL: 2400 mg/m³ (Vacated) STEL: 1000 ppm TWA: 1000 ppm TWA: 2400 mg/m³	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m³

Component	Quebec	Mexico OEL (TWA)	Ontario TWAEV
Acetone	TWA: 500 ppm	TWA: 1000 ppm	TWA: 500 ppm
	TWA: 1190 mg/m <sup>3</sup>	TWA: 2400 mg/m <sup>3</sup>	STEL: 750 ppm
	STEL: 1000 ppm	STEL: 1260 ppm	
	STEL: 2380 mg/m <sup>3</sup>	STEL: 3000 mg/m <sup>3</sup>	

NIOSH IDLH: Immediately Dangerous to Life or Health

# **Personal Protective Equipment**

Eye/face Protection

Skin and body protection Respiratory Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Wear appropriate protective gloves and clothing to prevent skin exposure.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid
Appearance Colorless
odor sweet

Odor Threshold
No information available.

pHNo information available.Vapor Pressure247 mbar @ 20 °CVapor Density2.0 (Air = 1.0)

Viscosity $0.32 \,\mathrm{mPa.s} \ @ \ 20 \,^{\circ}\mathrm{C}$ Boiling Point/Range $56\,^{\circ}\mathrm{C} \ / \ 132.8\,^{\circ}\mathrm{F}$ Melting Point/Range $-95\,^{\circ}\mathrm{C} \ / \ -139\,^{\circ}\mathrm{F}$ Decomposition temperature $> 4\,^{\circ}\mathrm{C}$ 

Flash Point -20°C / -4°F Evaporation Rate 5.6 (Butyl Acetate = 1.0)

Specific Gravity0.790SolubilitySoluble in water

log Pow No data available
Molecular Weight 58.08
Molecular Formula C3 H6 O

# **10. STABILITY AND REACTIVITY**

# 10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents, Strong reducing agents, Strong bases,

Peroxides

Hazardous Decomposition Products Carbon monoxide (CO<sub>2</sub>), Formaldehyde,

Methanol

Hazardous Polymerization Hazardous polymerization does not occur.

**Hazardous Reactions.** None under normal processing..

# 11. TOXICOLOGICAL INFORMATION

#### **Acute Toxicity**

**Component Information** 

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	
Acetone	5800 mg/kg (Rat)	Not listed	Not listed	

Irritation Irritating to eyes and skin

**Toxicologically Synergistic** 

Products

Carbon tetrachloride; Chloroform; Trichloroethylene; Bromodichloromethane;

Dibromochloromethane; N-nitrosodimethylamine; 1,1,2-Trichloroethane; Styrene; Acetonitrile,

2,5-Hexanedione; Ethanol; 1,2-Dichlorobenzene

**Chronic Toxicity** 

Carcinogenicity There are no known carcinogenic chemicals in this product

**Sensitization** No information available.

Mutagenic Effects Mutagenic effects have occurred in experimental animals.

**Reproductive Effects** Experiments have shown reproductive toxicity effects on laboratory animals.

**Developmental Effects**Developmental effects have occurred in experimental animals.

**Teratogenicity** Teratogenic effects have occurred in experimental animals..

Other Adverse Effects The toxicological properties have not been fully investigated.. See actual entry in RTECS for

complete information.

**Endocrine Disruptor Information** No information available

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Acetone	Not listed	Leuciscus idus: LC50 =	EC50 = 14500 mg/L/15 min	EC50 = 39 mg/L/48h
		11300 mg/L/48h	_	EC50 = 12700 mg/L/48h
		Salmo gairdneri: LC50 = 6100		EC50 = 12600  mg/L/48h
		mg/L/24h		

Persistence and Degradability Readily biodegradable.

Bioaccumulation/ Accumulation No information available

Mobility .

Component	log Pow
Acetone	-0.24

# 13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Acetone - 67-64-1	U002	-

# 14. TRANSPORT INFORMATION

DOT

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3 Packing Group II

TDG

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3 Packing Group II

**IATA** 

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

# 14. TRANSPORT INFORMATION

# IMDG/IMO

UN-No UN1090 Proper Shipping Name ACETONE

Hazard Class 3
Packing Group ||

# 15. REGULATORY INFORMATION

#### International Inventories

Component	TSCA	DSL	NDSL	<b>EINECS</b>	<b>ELINCS</b>	NLP	PICCS	<b>ENCS</b>	AICS	CHINA	KECL
Acetone	Χ	Χ	-	200-662-	-		Χ	Χ	Χ	Χ	Χ
				2							

#### Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

### **U.S. Federal Regulations**

TSCA 12(b) Not applicable

SARA 313 Not applicable

# SARA 311/312 Hazardous Categorization

Acute Health HazardYesChronic Health HazardNoFire HazardYesSudden Release of Pressure HazardNoReactive HazardNo

#### **Clean Water Act**

Not applicable

### Clean Air Act

Not applicable

\_\_\_\_\_

#### **OSHA**

Not applicable

#### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Component	Hazardous Substances RQs	CERCLA EHS RQs
Acetone	5000 lb	-

# **California Proposition 65**

This product does not contain any Proposition 65 chemicals.

# State Right-to-Know

Component	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Acetone	X	Х	Х	•	Х

### **U.S. Department of Transportation**

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

# **U.S. Department of Homeland Security**

This product contains the following DHS chemicals:

Component	DHS Chemical Facility Anti-Terrorism Standard
Acetone	2000 lb STQ

# Other International Regulations


Mexico - Grade Serious risk, Grade 3

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### **WHMIS Hazard Class**

B2 Flammable liquid D2B Toxic materials



# 16. OTHER INFORMATION

Prepared By Regulatory Affairs

Thermo Fisher Scientific

Email: EMSDS.RA@thermofisher.com

Creation Date 28-Apr-2009

Print Date 07-Mar-2011

**Revision Summary** "\*\*\*", and red text indicates revision

#### Disclaimer

The information provided on this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of MSDS**